VALUE AND RELIABILITY.

MERITOR RED BRAKE CHAMBERS (PARK AND SERVICE)



Meritor

FOR A WORLD THAT'S ALWAYS ON[™]

PARK AND SERVICE BRAKE CHAMBERS

For over 100 years Cummins-Meritor has been a leader in axle and braking systems for heavy vehicles. Meritor Red is an extended range of aftermarket braking components brought to you by one of the industry's most trusted names. Our new Brake Chambers are the latest addition to the line-up that delivers confidence and reliability you can count on.

FEATURES AND BENEFITS

Features	Benefits
Sealed spring brake (rear section)	Safety feature to prevent operator harm
Heavy-duty internal construction and housings	Reduces vibration and fatigue
Corrosion protected air springPowder coated steel end caps	 Enhances performance with protection for parts providing better durability and longevity with use
High force parking spring	Confidence in steep parking situations
Double push rod guide and O-ring	Leak protection and wear resistance
1 year on highway warranty	Certainty for maintenance planning
Includes release tool and mounting hardware	Ease of installation and removal

SPECIFICATIONS

Size 24/24, 2.5" stroke AE J1469 & J2318 compliant Standard Service, emergency port holes 3/8-18 NPTF) and distance tween mounting studs (4.75") Size 24/30, 2.5" stroke AE J1469 & J2318 compliant candard Service, emergency port holes (3/8-18 NPTF)		VILINITED KMS VILINITED KMS VILINITED KMS VILINITED KMS BRAKE CHAMBER DIAGRAM Premium diaphragms ensure longevity of operation Premium diaphragms ensure longevity of operation 4.6mm thick
AE J1469 & J2318 compliant	Û	Premium diaphragms ensure Powder coating for longevity of operation wear protection
and distance between mounting studs (4.75")		Springs provide linear output & 200,000+ parking life cycles Grac high st mountin
Size 30/30, 2.5" stroke AE J1469 & J2318 compliant andard Service, emergency port holes (3/8-18 NPTF) and distance between mounting studs (4.75")		Sealed spring brake (rear section) for OH&S
Size 36/36, 2.5" stroke SAE AE J1469 & J2318 compliant Standard Service, mergency port holes (3/8-18 NPTF) & distance between mounting studs (4.75")		Meritor Heavy Vehicle Systems Austr 50 Calarco Drive Derrimut, VIC 3026 AUSTRALIA (03) 8353 6050 meritorpartsonline.com
	E J1469 & J2318 compliant andard Service, emergency port holes (3/8-18 NPTF) and distance between mounting studs (4.75") ize 36/36, 2.5" stroke SAE E J1469 & J2318 compliant Standard Service, hergency port holes (3/8-18 IPTF) & distance between	E J1469 & J2318 compliant andard Service, emergency port holes (3/8-18 NPTF) and distance between mounting studs (4.75") ize 36/36, 2.5" stroke SAE E J1469 & J2318 compliant Standard Service, hergency port holes (3/8-18 IPTF) & distance between mounting studs (4.75")