

MERITOR® R301 23,000 LBS (GAWR) OEM BRAKE LINING




MERITOR®









IDEAS DRIVING RESULTS

COMPREHENSIVE DESIGN & SOLID
CONSTRUCTION ENSURES RESILIENCE &
LONG LIFE



TECHNICAL DATA - TYPICAL TEST RESULTS



TEST PARAMETERS	
Axle Rating	23,000 lbs
Brake Type and/or Size	16.5" x 7" Meritor Q Plus
Wheel Load	11,500 lb
AL Factor	180
Rolling Radius	20.8
Drum Weight	113 lbs
PROPERTIES	
Gogan Hardness	34
Specific Gravity	1.92
Flexural Strength	4,700 psi
Temperature Range	to 650°F
Material	Non-Asbestos
SAE J661A	
Normal Friction COF	.45° (F)
Hot Friction COF	.40° (F)

FEATURES AND BENEFITS

- Rated 23,000 lbs. GAWR at 180 AL (T30 chamber x 6.0" slack adjuster)
- Engineered for demanding applications where excellent wear characteristics are needed
- Preferred as the lining of choice for many OEM tractor production brakes
- Ideal for truck, tractor, trailer, school bus and heavy hauling applications, such as refuse and construction
- Excellent choice for hauling general cargo, grain and liquids
- Versatile performance in a variety of applications on or off highway in various terrain conditions



Meritor Heavy Vehicle Systems
 50 Calarco Drive
 DERRIMUT VIC 3030
 AUSTRALIA

Phone: (+61 3) 8353 6050
 Fax: (+61 3) 8353 6060
 Email: cvaau.sales@meritor.com

meritorpartsonline.com
meritor.com