

# CROSS-REFERENCE



Specifications					Self-Adjusting			Manual Adjusting								
Clutch Size	Spline Diameter and No. of Splines	Flywheel Bore Opening	Number of Springs	Clutch Torque (must exceed engine torque)	Eaton Solo Advantage™	EUCLID Self-Adjusting Clutch	Eaton Solo Advantage™ with Pre-Damper	Eaton Easy Pedal Advantage™ with Pre-Damper	Eaton Easy Pedal Advantage™	EUCLID Easy Pedal Effort	EUCLID Standard Pedal Effort	EverTough™ by Eaton	ValueClutch™ by Eaton	Eaton Easy-Pedal™ (remanufactured)		
15 1/2"	2" - 10	7"	8	1070							E107091-83B		107091-83B			
				1250							E107091-77B		107091-77B			
				1400							EP108391-81	E107091-81B	108391-81AM	107091-81B	108391-81MO	
		8.5"	10	1650								EP108391-74	E107091-74B	108391-74AM	107091-74B	108391-74MO
				1860								EP108391-93		108391-93B		
				2050								EP108391-93H				
				1650	209701-51	ESA209935-51				208925-51	EP108935-51	E107935-51B	108935-51AM	107935-51B	108935-61MO	
				1760	209701-61					208925-61	EP108935-91		108935-61AM	108935-94	108935-61MO	
				1650	209701-91					208925-91	EP108935-51	E107935-51B	108935-91AM		108935-91MO	
		10"	9 (Mack and Volvo 11L & 13L)	1760	209701-92				208925-92							
				2050		ESA209935-51H					EP108935-91					
				1700	209701-82	ESA209925-82	209701-34	208925-34	208925-82	EP108925-82	E107925-82	108925-82AM	107925-82	108935-82MO		
				209701-85		209701-29	208925-29	208925-85								
				1750	209701-21		209701-34	208925-34	208925-24							
				1760		209701-29	208925-29	208925-19								
1860	209701-20				209701-30	208925-30	208925-20	EP108925-25		108925-20AM						
2050	209701-25			ESA209925-25	209701-35	208925-35	208925-25	EP108925-25		108925-25AM						
2250								EP108925-32H								
14"	2" - 10	7"	8	1000	N/A	N/A	N/A	N/A					107034-61B	108034-61MO		
				1150							108034-61B	EP108034-61B	E107034-61B		107034-61B	
				1400								EP107034-57B	E107034-57B		107034-57B	
												EP108034-82B	EP108034-82B	E107034-57B		108034-82MO
									EP108050-59B	EP108050-59B	E107050-59B	108050-59AM	107050-59B	108050-59MO		

Specifications					Manual Adjusting	
Clutch Size	Spline Diameter	Flywheel Bore Opening	No. of Discs	Clutch Torque (must exceed engine torque)	Eaton	EUCLID Easy Pedal Effort
14"	1 3/4"	F l y e a w l t h e	1	620	107683-5 107683-5MO	EP107683-5
			2	900	107237-22 107237-10 107237-10MO	EP107237-22
	2"		900		107342-12	EP107342-12
			950		107342-24	EP107342-24